2011

R4 Series User Manual

Forwell Wireless Ltd.

2011-4-27

Copyright Declaration

Sales	**Phone**	**+86-755-26624211**
	E-mail	sales@forwellwireless.com
	FAX	+86-755-26621490
Post	2-4A,Chaguang Industrial Park, Nanshan District,Shenzhen,Guangdong Province P.R.China	
Web	http://www.forwellwireless.com	

Catalog

Chapter 1 Instruction Manual Introduction

This chapter is about the related operation information of the R4 Routers. It is the best instruction manual for installing and using R4 series.

1. Purpose
2. Application Fields
3. Version Information
4. Technical Support

1.1 Purpose

This Instruction Manual is mainly for the installation and test of the R4 series of Forwell Wireless.

1.2 Application Fields

This Instruction Manual is suitable for the users who has certain knowledge of computer network and electronic technology, network device administrators and other management personnel who need to use R4 series.

1.2 Version Information

According to the requirement of the market and the users, we will make some functional adjustment and technical improvement to the R4 series. Below table includes all the versions of the R4 series of Forwell Wireless and revision reasons in different periods.

Table-1.1：Version Information

Version No.	Revision Department	Related Department	Date	Revised Content
1.0.0	R&D Center	Sales, Technical Engineer	2010.12	First publish
2.0.0	R&D Center	Sales, Technical Engineer	2011.1	Add some function and make

				adjustments to hardware
2.1.1	R&D Center	Sales, Technical Engineer	2011.3	Add function

1.3 Technical Support

In order to solve the problems more quickly. Please contact us by:

- ☎ Tel：

  Service Hot-line: 0755-88839200

- ✉ E-mail:

  Technical Support: support@forwellwireless.com

For more information, please visit our website www.forwellwireless.com.

Chapter 2 Product Introduction

This chapter mainly describes the function of R4 series and field of application.

1. *Brief Introduction*
2. *features*
3. *application*
4. *Product model*

2.1 Brief Introduction

With the development of mobile communication technology, the mobile data communication network using GPRS/CDMA/EDGE/EVDO/TD-SCDMA/HSDPA/HSUPA has covered many regions in the world. And network is very stable. All these make a larger market for wireless terminals. Because different industries have different applications and different information needs, so the industry application solutions provided by the mobile communication operators must satisfy both the common needs and the special individual needs of the industry users perfectly. Therefore, in recent two years, based on the needs of industry users, Telecommunication, Telecom Operator do innovative practice energetically in mobile application and provide solutions to meet the unique needs of the users. Being different with the popular data requirements, indusry application is very professional. Different industry users need different terminals. So hardware and software development and system integration must be accord with different industry needs. So by analysing the different industry application features in recent years and according to the network features and the actual condition of the network operators, Forwell Wireless Ltd launched the individually designed R4 series.

R4 series provide users the high-speed, always-online and transparent-data-transmission communication network. In order to meet the needs of Electronic Power System Automation, Industry Monitoring, Transportation Management, Weather, Environment Protection, Pipe Network Monitoring, Finance and Bond industries, by using 2G/3G network R4 series achieve the transparent data transmission function. In the meantime, considering the network needs of every department, on the basis oR4 series developed the

R4 products which have RS232/485 interface are high-performance,industry-use and external.

2.2 function features

- Supports EV-DO RevA/Rev0, 1xRTT, HSUPA, HSDPA, UMTS, EDGE & GPRS network
- 1 port 10/100 Ethernet LAN switch with LAN / DMZ configurable zones
- 3G module Built-in
- Support WiFi 802.11b/g/n
- RS-232 port offer a transparent channel for M2M application
- IPSec-based VPN client w/DES, 3DES, AES
- Stateful Packet Inspection Firewall
- Supports dynamic or static IP addresses assigned by cellular carriers
- Support APN/VPDN network

2.3 application Fields

- Video Surveillance



- Financial Service(ATM&POS)



2.4 Product model

R49 HSUPA Router
R48 TDSCDMA Router
R47 HSDPA Router
R46 EVDO revA Router

R461Y232 EVDO revA Router
R44 EDGE Router
R43 CDMA Router
R42 GPRS Router

Chapter 3 Hardware Installation

This chapter mainly describes the appearance, model and function of R4 series and how to install and set the configurations.

1. *Overall Dimension*
2. *Accessories Description*
3. *Installment*

3.1 Overall Dimension



3.2 Accessories Description

Name	Entires	Quantity	Describe	Picture
Device	piece	1	Standard	
Power	piece	1	12V1A	
antenna	piece	2	Standard	
Network cable	piece	1	Standard	
Usermanual	piece	1	Standard	CD-ROM

3.3 Installment

R4 series should be installed and configured properly before putting in service.The installation and configuration should be done or supervise by qualified engineer.

Attention:

Don’t install R4 series or connect/disconnect its cable when it is power on.

3.3.1 SIM/UIM card installed

Before loading SIM/UIM card, please open back cover. Up gently, gap outwards, press to make the card fixed.

Attention: *SIM/UIM card does not reach the designated position, the equipment can not find a card, can't work normally.*

3.3.2 The installation of terminal blocks

R4 use pluggable terminals to connect the user's data and the power supply. Spacing: 3.81mm， 10 Pin; user data and power supply suggestion: 14~24AWG. Please refer to the Table 2-4 for the interface definition of the power cable and connection sequence. Specific interface definition of the power cable and connection sequence you can read on the labels of R4 products.

Using 14~24AWG cable and referring to R4 products labels or the belowed interface definition and connection sequence, you need to use the oblate screw driver to fix the cable to the connecting jacks of the pluggable terminal. After successfully connection, you need to insert the terminal into the corresponding position in the bottom of the R4 products.

Notes: Connection sequence should be accurate。Cable's insulating striping length is about 7mm. (For safety, insulating striping length should be not too long.). please refer to the picture.

Attention:

1. *The power cable should be connected correctly .We "suggest double check before switch it on .Wrong connections may destroy the equipment.*
2. *Power terminals:Pin 1 and Pin 2;*
3. *Here： Pin 2 is "GND",PIN 1 is power input "Vin"(DC7~30V).*

3.3.3 Teiminal signal definition

PIN	Signal	Description	Note
1	Vin	+7-30V DC Input	Current：12V/1A
2	GND	Ground	
3	Tx	Transmit	
4	Rx	Receive	
5	PGND	Ground	
6	Reset	Reset	Reset Pin has the same function with reset button. In the usage,it needs to be short connected to the GND. After giving the device a 1 sec low level, it will reboot.3 seconds, the device will restore factory settings
7	SPI-I（IO0）	General Purpose I/O	
8	SPI-O IO1）	General Purpose I/O	
9	SPI-CLK IO2）	General Purpose I/O	
10	SPI-EN IO3）	General Purpose I/O	

3.3.4 Grounding

To ensure a safe ,stable and reliable R4 series operation,Router cabinet should be grounded properly.

3.3.5 Power Supply

R4 series can be applied to complicated external environment and usually the power range is very large. So in order to fit the complicated application environment and improve the stability of the system, R4 series is designed with advanced power management technology. The DC power supply electronic to the device via the pluggable terminal PIN 2(GND) and PIN 1(Vin).Please refer to the above table for the detail definition of the terminal.

Normally, R4 series input powers supply is +7～+30V. the standard configuration is 12V/1A.

3.3.6 Check Network Status

Please connect the antenna after you successfully connect to the cable. And then insert the valid SIM/UIM card and provide the power to the R4 series via the cable. After provide the power to R4, if the RUN light start to blink in a few seconds, that means the system start-up is normal; if the Online light works, that means the network has been found; if the VPN light works, that means VPN tunnel has been set up. Please refer to the below table for the situation of the indication lights.

LED	Indication Light	Description
Run	On for 3 seconds	On for 3 seconds after power supply
	blink	System set-up normally
	Off or still on after 3 seconds	System set-up failure
Lan	blink	Data transmission in Ethernet
	Off	Ethernet connection abnormal
VPN	On	VPN tunnel set-up
	Off	VPN tunnel set-up failure



Online	On	Access to the Internet	
WIFI	On	Enable	
	Off	Disable	

Chapter 4 Software configuration

1. *Overview*
2. *How to log into the Router*
3. *How to config web*

4.1 Overview

R4 series routers with built-in WEB interface configuration, management and debugging tools, user should configure the parameters first;and it could be altered the parameters flexibility and software upgrades and simple testing.
user can set up and manage the parameters of the router on its interface ,detail step as belows :.

4.2 How to log into the Router

4.2.1 network Configuration of the Computer.

The router default parameters as follow
IP: 10.10.10.254, sub mask: 255.255.255.0.

There are two ways to set the PC's IP address.

1. Manual setting
   Set the PC IP as 10.10.10.xxx (xxx = 1~253), subnet mask: 255.255.255.0, default gateway: 10.10.10.254, primary DNS: 10.10.10.254.
2. DHCP
   Choose "Obtain an IP address automatically" and "Obtain DNS server address automatically".
   After IP setting, check it by ping. Click Windows start menu, run, execute "cmd" command. Input "ping 10.10.10.254" in the DOS window.

```
C:\>ping 10.10.10.254

Pinging 10.10.10.254 with 32 bytes of data:

Reply from 10.10.10.254: bytes=32 time<1ms TTL=64
Reply from 10.10.10.254: bytes=32 time<1ms TTL=64
Reply from 10.10.10.254: bytes=32 time<1ms TTL=64
Reply from 10.10.10.254: bytes=32 time<1ms TTL=64

Ping statistics for 10.10.10.254:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

This information means the connection is ok.

```
C:\>ping 10.10.10.254

Pinging 10.10.10.254 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 10.10.10.254:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
```

This information means the connection is failure. If so, please check the network cable connection and IP address setting.

4.2.2 log into Router

- Open the Web browser, and type http://10.10.10.254 into the address field and press Enter botton in your computer keyboard.
- Type User Name “admin” and Password “admin” in the pop-up Login Window, and then press the “Apply” button.

- If you type into the correct User Name and Password, you will get the access into the Router's Web Management Page.



4.3 config through web

4.3.1 Main Menu as below Picture

4.3.2 Operation Mode



- **Bridge:** All ethernet and wireless interfaces are bridged into a single bridge interface.
- **Gateway:** The first Ethernet port is treated as WAN port. The other

Ethernet ports and the wireless interface are bridged together and are treated as LAN ports.

- **AP Client:** The wireless interface is treated as WAN port and the wireless AP interface and the Ethernet ports are LAN ports.
- **NAT:** Network Address Translation

4.3.3 WAN Settings



- WAN Connection Type support: Static IP, DHCP, PPPoE, L2TP, PPTP, 3G.
- USB Modem: System supports the follow module: HUAWEI EM560（for R88 TD-SCDMA）, HUAWEI EM660/THINKWILL MI600(for R86 EVDO), and HUAWEI EM770/LONGSUNG-U6300/U5300(for R89 HSPA). Please choose right USB modem.
- 3G SIM PIN: enter PIN code if necessary.
- Operation Mode: always online, connect on demand, connect on time. The default mode is always on line.
- MAC Clone: enable and disable the MAC clone function.



- **Mobile MSP parameters:** edit the MSP parameters.
- **MSP Name**: any name is ok
- **3G network type**: you can choose right network here.
- **Dialing Number**: Input the Dialing Number you get from ISP. For example, China Telecom (#777)
- **Initial Command String:** you need to input the username and password or APN offered by ISP with our Initial command

  R46 EVDO:pleaseinput: at\^pppcfg=\"username\",\"password\" Take China Telecom (both username and password are "CARD")as a sample: we input this command at\^pppcfg=\"CARD\",\"CARD\"
  (HUAWEI_EM660/Thinkwill MI600)

  R47/R49 HSPA: at+cgdcont=1,\"IP\",\"APN\", Take China Mobile(Their APN is 3gnet) as a sample: we input this command at+cgdcont=1,\"IP\",\"3gnet\",
  (HUAWEI_EM770/U5300/U6300/GaoRan280)

  R42a GPRS: at+cgdcont=1,\"IP\",\"APN\", as a sample: we input this command at+cgdcont=1,\"IP\",\"cmnet\",

  R43a CDMA: at+zpidpwd=username,password , as a sample:we input this command at+zpidpwd=card,card
- **Username and Password:** input them.
- **Authenticate Type:** PAP/CHAP, the default setting is auto.

MSP list: This list is produced automatically once you finish the above mobile MSP parameters.just choose the right MSP parameters and corresponding module(3G USB modem), and click Apply, then it will dial.

For example, we use R49 HSPA router to dial:





4.3.4 LAN Settings



Setting the LAN parameters, include IP address, sub mask, VLAN, DHCP, etc.

4.3.5 DHCP Client



List the Clients which gain IP address from DHCP .

4.3.6 Configure Static Routing

This section mainly introduce what is Routing Table and how to configure

static router.

- Routing Table

  This page shows the key routing table of this router.

Current Routing table in the system:

No.	Destination	Netmask	Gateway	Flags	Metric	Ref	Use	Interface	Comment
1	255.255.255.255	255.255.255.255	0.0.0.0	5	0	0	0	LAN(br0)	
2	10.10.10.0	255.255.255.0	0.0.0.0	1	0	0	0	LAN(br0)	

- New Static Router

  This page is about how to set static routing function of the router.



§ **Destination**: please enter Target Host or IP network segment
§ **Range**: Host or Network can be chosen
§ **Gateway**:IP address of the next router.
§ **Interface**: You can choose the corresponding interface type.
§ **Comment**: some notes
Notice:

- Gateway and LAN IP of this router must belong to the same network segment.
- If the destination IP address is the one of a host, and then the Subnet Mask must be 255.255.255.255.
- If the destination IP address is IP network segment, it must match with the Subnet Mask. For example, if the destination IP is 10.0.0.0, and the Subnet Mask is 255.0.0.0.

4.3.7 Qos(Quality of Service)

QoS (Quality of Service) Service Quality, is one of the network security mechanism, is used to solve the network to delay and block of a kind of technology. In normal conditions, if the network only used for particular no time limit of application system, does not need QoS, such as the Web application, or E-mail setting, etc. But for critical applications and multimedia applications is very necessary. When the network overload or congestion, QoS can ensure that important business from delay or discarded, at the same time, to guarantee that the network of efficient operation.

The Quality of Service Setting:

The interface on a router, find QoS quality service set up options, the configurations. As shown in figure.



First, choose open QoS function, the user can need according to custom upload bandwidth and download bandwidth, can also through the drop-down list to choose the appropriate bandwidth, and click submit.

Then, the input to the speed limit of LAN IP address, fill out the upload bandwidth and descending bandwidth, it should be noted, fill in to pay attention to the Numbers behind the unit made clear, 10 K or 10 M, click the Add.



Finally, as you can see, just add IP information is in list directory, in Numbers and played the hook on set up a success.

pictorial view:



4.3.8 VPN

4.3.8.1 IPSEC





- **IPsec connect name**: make sure the name in client and server are same, we suggest to use domain name(111.vpn1.com). if you want to build a point-to-point channel, the IPsec name have to be written as DEV+equipment ID+name(DEV281250D52F2A1452.vpn1.com), and make sure both the client and server are inputing Client equipment ID. You can find R8's ID in the Status interface.
- **Service Mode**: Server/Client
- **Mode**: Main/Aggressive. The Aggressive mode is commonly used.
- **Remote Gateway**: This choice just appears in the Client mode and it is used to fill the IP address in the Server.
- **Local IP address**: Fill LAN IP of this device. You can fill an IP or a network segment.
- **Remote IP address**:Fill the IP of the other router.
- **Authentication**: Commonly, Pre-Shared Key is chosen. And the Client and Server must choose the same key.
- **Advanced AKE settings:** There are some encryption methods in this field. You must use the settings in this field when VPN tunnel needs to be built between R8 and other brand VPN server.

- **Example: Connected cisco 7200 and R4**

  How to config R4 as VPN clinet

  IPsec Name:make sure the name in client and server are same, we suggest to use domain name(111.vpn1.com). if you want to build a point-to-point channel, the IPsec name have to be written as DEV+equipment ID+name(DEV281250D52F2A1452.vpn1.com), and make sure both the client and server are inputing Client equipment ID. You can find R8's ID in the Status interface.





How to config cisco 7200 as VPN Server

```
crypto keyring jordan
 pre-shared-key hostname jordan key test

 crypto isakmp profile jordan
  description china SZ shenzhen
  keyring jordan
  match identity host jordan
  keepalive 60 retry 10

 crypto ipsec transform-set vpnset esp-des esp-sha-hmac

 crypto ipsec profile jordan
set transform-set vpnset
set isakmp-profile jordan

 crypto dynamic-map jordan 1
  set security-association lifetime kilobytes 536870912
  set security-association lifetime seconds 43200
  set transform-set vpnset
  set isakmp-profile jordan
  reverse-route
   crypto map COREVPN 26 ipsec-isakmp dynamic jordan
```

4.3.8.2 PPTP



this function in the device just works as Client.

4.3.8.3 L2TP



this function in the device just works as Client.

4.3.9 DTU Settings



This section is mainly about DTU settings.

- **DTU status:** open and close DTU
- **Baudrate:** support 4800/9600/19200/38400/57600/115200bps
- **Link Type:** Server link or Client link can be chosen in the DTU config table. If use it as Server, we suggest you to use fixed IP of the SIM card.
- **Multiple-path Backup**: the router can support 4 Server IP at most to meet the need for multiple-path data backup.
- **Heart Beat function**: You can define heart beat time and heat beat information. So that Server can use the heart beat information to identify DTU.
- **Data content:** the largest package contents are 3KB. The interval between packets can be adjusted through change "send data timeout".

4.3.10 SMS/Voice Control（it is only used for R46B/R49B）



This section is to introduce how to wake up the router from SMS or Voice.

- **SMS/Voice status:** open(on) or close(off) this function.
- **Send respond SMS:** When the router receive a message, it will reply one piece if you choose"on"..
- **Voice Command:** 4 choices(close, 3G link up, 3G link down, 3G link up or down); perform the corresponding action according to what you have chosen. (Note:at present, Voice function do not support phone number filtering.)
- **Telephone Number Settings:** 10 numbers can be set at most, which you can send SMS from these phone numbers.
- **Command Settings:** Sending order by mobile phone can open "3G link up" and "3G link down".

Note: SIM Card inserted in the router must support SMS or Voice.

4.3.11 GPS(OPTIONAL)

Due to different application requirements, R4 3G takes all these special r equirements into consideration, so R4 3G provide you GPS service. Detailed settings as below:



- GPS Settings： 1.GPS Action:enable/disable
  2.GPS Send to:Serial or TCP/IP
- Serial Settings： 1.Baudrate:default 115200
  2.Parity:default none

3.Datebit:default 8
4.Stopbits:default 1
5.Flow Control:default none

- GPS To TCP/IP Settings: 1.Socket Type:TCP/UDP
  2.Server:Server IP address
  3.Port:Server Port

4.3.12 Wirless settings

4.3.12.1 Basic Wireless Settings



Wireless Network	
Radio On/Off	RADIO OFF
Network Mode	11b/g/n mixed mode
Network Name(SSID)	Forwell Hidden ☐ Isolated ☐
Multiple SSID1	Hidden ☐ Isolated ☐
Multiple SSID2	Hidden ☐ Isolated ☐
Multiple SSID3	Hidden ☐ Isolated ☐
Multiple SSID4	Hidden ☐ Isolated ☐
Multiple SSID5	Hidden ☐ Isolated ☐
Multiple SSID6	Hidden ☐ Isolated ☐
Multiple SSID7	Hidden ☐ Isolated ☐
Broadcast Network Name (SSID)	◉ Enable ○ Disable
AP Isolation	○ Enable ◉ Disable
MBSSID AP Isolation	○ Enable ◉ Disable
BSSID	00:10:18:01:05:34
Frequency (Channel)	2437MHz (Channel 6)

The basic parameters of Wi-Fi setting.
The Radio function enable and disable.
The network mode supports 802.11 b/g/n (draft).
Support multi-SSID up to 8.

4.3.12.2 Wireless Security/Encryption Settings

Select SSID	
SSID choice	Forwell



The SSID select from multi-SSID setting.
Security mode include: disable, open, share, wep auto, WPA, wpa-psk, wpa2, wpa2-psk, wpa-psk/wpa2-psk, wpa/wpa2, 802.1X.
Access policy: setting the MAC list for access or deny.

4.3.13 Firewall

4.3.13.1 MAC/IP/Port Filter Settings





This section is mainly about MAC/IP/Port filter settings

- **Basic Settings:** Open the filter setting and set the filtering principle.
- **MAC address:** Fill the MAC address which needs to filter.
- **Destination IP:** IP of the target computer(the computer which the data packet will be sent to)
- **Destination Port Range:** port range of target computer
- **Source Port Range:** port range of the computer which sends data

4.3.13.2 Port Forwarding



Port forwarding is the process that your router or firewall uses to sort the right kind of network data to the right port. Computers and routers use ports as a way to organize network data. Different types of data, such as web sites, file downloads, and online games, are each assigned a port number. By using port forwarding, the router or firewall sends the correct data to the correct place.

- Virtual Server Settings: open and close Settings.
- IP address: fill the IP address of forwarding.
- PortRange: fill the Port of forwarding.

4.3.13.3 DMZ Host



In computer networking, DMZ is a firewall configuration for securing local area networks (LANs).

- DMZ Settings: open and close Settings.
- DMZ host IP Address: Please Enter the IP address of the computer which you want to set as DMZ host

Note: When DMZ host is setted, the computer is completely exposed to the external network, the firewall will not influence this host.

4.3.13.4 System Security



Include Remote management,Ping from WAN Filter and SPI(Stateful Packet Inspection).

4.3.13.5 Content Filter Settings



You can setup Content Fillter to restrict the improper content access,including Webs Content Settings,URL filter and Host Filter.

4.3.14 Administration

4.3.14.1 Management

- Select Language
- Adminstrator Settings. The default both are admin.
- NTP Settings



DDNS: support Dyndns.org/freedns.afraid.org/www.zoneedit.com/www.no-ip.com

4.3.14.2 Reboot Settings



This function will detect the status of 3G by ping and complete the corresponding actions according to the ping result。

- Check the box, start the net detection restart function.
- Detection method (PING): fill the server domain name or IP, and then click the detection button, and detect if the fill-in is right.
- Detection interval time (second): the interval time between the first detection and the second detection is 60-86400 seconds.
- Detection counter: if you can't get the right result by ping when the detection frequency is the same as the fill-in times, the device will restart.
- Restart the counter before the detection function get into dormant state & detection function dormant time: this will protect the device against the damage caused by the continuous restarts, which are caused by the ping failure by the result of the fault in filling the server domain name. After several times of restarts, the device will get into the dormant state. After that the detection will continue, and now the counter in flash will become zero and recount.

Note: This function will be only valid only in 3G permanent on-line and dialing according to the setting time,other states not.In setting ,firstly you must detect if the filled-in server domain name or IP is valid.

4.3.14.3 Upgrade Firmware



Upgrade the firmware to obtain new functionality. It takes about 2 minutes.

4.3.14.4 Parameter Management



Here you can make a backup of current settings or restore previous settings of the router .

- **Export settings:** click 'export' to export configuration files and then select save path.
- **Import settings:** click 'browse', select previous backup configuration files and then click 'Import'. Then all the previous settings will be recovered.
- **Load Factory Defaults:** click 'Load Default' then all settings will be restored to factory settings. This is not recommended in order to avoid the loss of important parameter

4.3.14.5 System state information

From the this page you can see the Router's basic running state.

- Product Model
- **Software Version**: software version reveals the status of software update.
- **Hardware Version**: 1.0.0
- **Device ID**: every device has a unique ID, which has two functions: 1, it is manageable; 2, it allows to use point to point in VPN.
- **System Uptime:** this time directly reveals router working hours.
- **Signal Strength:** reveals the current network state of 2G/3G. 0 and 99 mean no signal.
- **Attachment state:** displays the current network attachment state, which can be set by users.
- **WPN IP address:** the IP expose when the router gets on internet.

4.3.14.6 Flow Statistics

WAN/LAN	
WAN Rx packets:	0
WAN Rx bytes:	0
WAN Tx packets:	18
WAN Tx bytes:	1476
LAN Rx packets:	1063
LAN Rx bytes:	100996
LAN Tx packets:	572
LAN Tx bytes:	440808

Display the statistics information of system flow.

4.3.14.7 System log



From the system log you can read the various situations after the system starts.